

Full Range Speakers

PORTABLE + INSTALLED

ONE CABINET. EVERY DETAIL.

Compact two-way systems with balanced voicing, predictable coverage and installation-ready hardware.

- Rotatable constant-directivity horn across the range
- Pole, floor-monitor and permanent-installation configurations
- Rugged enclosures with integrated handling points



Performance targets for project planning - final production data subject to validation

MODEL RANGE

MODEL	CONFIGURATION	AES POWER	FREQUENCY RANGE	MAX SPL	COVERAGE	IMPEDANCE	WEIGHT
AC-FR8	8 in + 1 in	250 W	68 Hz-20 kHz	123 dB	90 deg x 60 deg	8 ohm	10.2 kg
AC-FR10	10 in + 1 in	350 W	58 Hz-20 kHz	126 dB	90 deg x 60 deg	8 ohm	14.5 kg
AC-FR12	12 in + 1.4 in	500 W	50 Hz-20 kHz	130 dB	90 deg x 60 deg	8 ohm	19.8 kg
AC-FR15	15 in + 1.4 in	700 W	44 Hz-20 kHz	133 dB	90 deg x 60 deg	8 ohm	26.7 kg

TYPICAL APPLICATIONS

Portable PA / Corporate events / Education / Hospitality / Performance spaces